



Snittringskoblinger

AISI 316TI

Med sertifikat iflg. EN 10204/3.1.B



Dimensjon		Reservering		Union	90° Albue	T-rør	Kryss
Utv.rørdia mm	PN	500 Z RL.nr.	Brilliant 500 B RL.nr.	505 G RL.nr.	506 W RL.nr.	507 T RL.nr.	508 K RL.nr.
4	LL 100	x	x	x	x	x	x
6	LL 100	x	x	x	x	x	x
	L 316	16500030	x	16500100	16501300	16502400	x
	S 630	16500030	x	x		x	x
8	LL 100	x	x	x		x	x
	L 316	16500040	x	16500200	16501400	16502500	x
	S 630	16500040	x	x		x	x
10	L 316	16500050	16500052	16500300	16501500	16502600	16507900
	S 630	16500050	16500052	x		x	x
12	L 316	16500060	16500062	16500400	16501600	16502700	x
	S 630	16500060	16500062	x		x	x
14	S 630	x	x	16500800	16502000	16503100	x
15	L 316	16500070	16500072	16500500	16501700	16502800	x
16	S 630	x	x	16500900	16502100	16503200	x
18	L 316	16500080	16500082	16500600	16501800	16502900	x
20	S 630	16500090	16500092	16501000	16502200	16503300	x
22	L 316	x	x	16500700	16501900	16503000	x
25	S 630	x	x	16501100	16502300	16503400	x
28	L 316	x	x	x	x	x	x
30	S 630	x	x	x	x	x	x
35	L 316	x	x	x	x	x	x
38	S 630	x	x	x	x	x	x
42	L 316	x	x	x	x	x	x
50	S 630	x	x	x	x	x	x



Snittringskoblinger

AISI 316TI

Med sertifikat iflg. EN 10204/3.1.B

						
Utv. rørdia mm	Dimensjon		Tippunion		90° Albue	
	Utv. Rørgj BSP	PN	510 geG RL.nr.		516 weR RL.nr.	
6	1/8"	S 630	16503500		x	
	1/4"	S 630	16503600		16510100	
	3/8"	S 630	16503700		x	
	1/2"	S 630	16503800		x	
	3/4"	S 630	16503900		x	
8	1/8"	L 315	16504000		x	
	1/4"	S 630	16504100		16510200	
	3/8"	S 630	16504200		16510300	
	1/2"	S 630	16504300		16510400	
10	1/8"	L 315	16504400		x	
	1/4"	S 630	16504500		16510500	
	3/8"	S 630	16504600		16510600	
	1/2"	S 630	16504700		16510700	
12	1/8"	L 315	16504800		x	
	1/4"	S 630	16504900		16510800	
	3/8"	S 630	16505000		16510900	
	1/2"	S 630	16505100		16511000	
14	1/4"	S 630	16505200		x	
	3/8"	S 630	16505300		x	
	1/2"	S 630	16505400		x	
	3/4"	S 630	16505500		x	
	1"	S 630	16505600		x	
15	3/8"	L 315	16505700		x	
	1/2"	L 315	16505800		16511100	
	3/4"	L 315	16505900		x	
16	3/8"	S 400	16506000		x	
	1/2"	S 400	16506100		x	
	3/4"	S 400	16506200		x	
18	3/8"	L 315	16506300		x	
	1/2"	L 315	16506400		x	
	3/4"	L 315	16506500		x	
20	1/2"	S 400	16506600		x	
	3/4"	S 400	16506700		x	
	1"	S 400	16506800		x	



Snittringskoblinger

AISI 316TI

Med sertifikat iflg. EN 10204/3.1.B

					
Utv. rørdia mm	Dimensjon		PN	Tippunion	90° Albue
	Utv. Rørgj BSP			510 geG RL.nr.	516 weR RL.nr.
20	1.1/4"	S	400	16506900	x
	1.1/2"	S	400	16507000	x
22	1/2"	L	160	16507100	x
	3/4"	L	160	16507200	x
	1"	L	160	16507300	x
25	3/4"	S	400	16507400	x
	1"	S	400	16507500	x
	1.1/4"	S	400	16507600	x
	1.1/2"	S	400	16507700	x